



ETL LISTED  
CONFORMS TO  
NFPA STD 79  
UL STD 508  
UL SUBJECT 2011  
CERTIFIED TO  
CSA STD C22.2 NO. 73

**HAAS** MILL MODEL  
DE-1/40

HAAS AUTOMATION, INC.  
2800 STURGIS RD, OXNARD, CA. 93030  
www.HAASCNC.com

SERIAL NUMBER.....	1215030	CE EAC UK CA
DATE OF MFG.....	05/2020	
VOLTAGE.....	220	
PHASE.....	3	
HERTZ.....	50/60	
FULL LOAD.....	40	AMPS
LARGEST LOAD.....	35	AMPS
SHORT CIRCUIT INTERRUPTING CAPACITY - 10,000 AMPS		
WIRING DIAGRAM.....	96	0204
SHORT CIRCUIT CURRENT - 5,000 AMPS RMS SYMMETRICAL		
ARC FLASH RATING: 208 - 240VAC MODELS HRC-1, 360-480VAC MODELS HRC-2		
NEMA TYPE 2 ENCLOSURE - FOR INDOOR USE ONLY. OVER CURRENT PROTECTION PROVIDED AT MACHINE SUPPLY TERMINALS.		
<b>Export Control Notice - This Machine Is an Export Restricted Product - Diversion Contrary to Law Is Prohibited</b>		
The export, re-export and in-country transfer of this machine are subject to United States Export Administration Regulations and may be subject to other export regulations as applicable, including but not limited to European Union export regulations.		
P/N 29-10048E Rev. A		













